

RP-Technik GmbH
 Hermann-Staudinger Straße 10-16
 63110 Rodgau

Operator RP Projektteam
 Telephone 06106 660280
 Fax
 e-Mail info@rp-group.com

RP-TECHNIK DOE029 ER-Light recessed, CBS / Data sheet emergency lighting



Luminaire: RP-TECHNIK DOE029 ER-Light recessed, CBS

Lamps: 1 x DOE029

Colour rendering index: 70
 Luminous flux: 140 lm
 Correction Factor: 1.000
 Emergency lighting factor: 1.00
 Emergency lighting luminous flux: 140 lm
 Light output ratio: 85.13
 Light output ratio (lower hemisphere): 100.00
 Light output ratio (upper hemisphere): 0.00

Glare valuation (Maximum luminous intensity [cd])

| | C0 | C90 | C0 - C360 |
|-----------------|------|-------|-----------|
| Gamma 60° - 90° | 1.4 | 112.1 | 112.1 |
| Gamma 0° - 180° | 34.6 | 112.1 | 112.1 |



Distance table for even escape routes

Mounting Height [m]

| Mounting Height [m] | | | | | |
|---------------------|------|------|------|-------|------|
| 2.50 | 1.68 | 4.16 | 8.30 | 12.61 | 5.45 |
| 3.00 | 1.74 | 4.49 | 9.14 | 14.13 | 5.80 |
| 3.50 | 1.71 | 4.74 | 9.64 | 15.34 | 5.64 |
| 4.00 | 1.60 | 4.89 | 9.31 | 16.13 | 4.54 |
| 4.50 | 1.36 | 4.92 | 8.20 | 15.84 | 3.35 |
| 5.00 | 0.87 | 4.84 | 7.30 | 15.14 | 2.08 |
| 5.50 | 0.00 | 4.62 | 4.84 | 13.76 | 0.00 |
| 6.00 | 0.00 | 3.61 | 3.61 | 10.98 | 0.00 |
| 6.50 | 0.00 | 2.82 | 2.82 | 8.63 | 0.00 |
| 7.00 | 0.00 | 1.94 | 1.94 | 4.68 | 0.00 |

The spacing table is based on the following parameters:

- Maintenance factor: 0.80
- Emergency lighting factor: 1.00
- Minimum illuminance on centre line: 1.00 lx
- Minimum illuminance on half of escape route width: 0.50 lx
- Diversity on the centre line max. 40 : 1
- Width of escape route: 2.00 m