



**Art.-Nr: AGR401WL-E**  
**CS\_VALUE\_LuminaireType.Rettungszeichenleuchte**  
**CS\_VALUE\_Supply.Einzelbatterie**  
**CS\_VALUE\_MountingMethod.Wandeinbau, Wireless Professional, CS\_VALUE\_BackupTime.1 h,**  
**CS\_VALUE\_RecognitionDistance.50m,**  
**CS\_VALUE\_IngressProtection.IP 40, CS\_VALUE\_Material.29,**  
**CS\_VALUE\_Color.Edelstahl**



The AGR is a zinc-diecast exit sign for recessed wall mounting and for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaires of the A-Series are equipped with modern LED illuminants and offer flexibility with changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838



[general.qrcode-more-infos](#)



## TEXT. TECHNISCHE-DATEN

~pim_attribute~Leuchtentyp	CS_VALUE_LuminaireType.Rettungszeichenleuchte
~pim_attribute~Montageart	CS_VALUE_MountingMethod.Wandeinbau
~pim_attribute~Erkennungsweite	CS_VALUE_RecognitionDistance.50m
~pim_attribute~Piktogramm	CS_VALUE_LuminairePictograph.Einzeln n.A.
~pim_attribute~Leuchtmittel	CS_VALUE_LightSource.LED
~pim_attribute~Gehauese-material	CS_VALUE_Material.29
~pim_attribute~Farbe	CS_VALUE_Color.Edelstahl
label.zuordnungsspeicher.Schutzart	CS_VALUE_IngressProtection.IP 40
~pim_attribute~Schlagfestigkeit	CS_VALUE_IKclass.IK ≥ 3
label.zuordnungsspeicher.Zertifizierungen	CS_VALUE_Certifications.11924, CS_VALUE_Certifications.11913
~pim_attribute~Schutzklasse	CS_VALUE_InsulationClass.2
~pim_attribute~Versorgung	CS_VALUE_Supply.Einzelbatterie
~pim_attribute~Ueberwachung	Wireless Professional
~pim_attribute~Ueberbrueckungszeit	CS_VALUE_BackupTime.1 h
~pim_attribute~Batterie	LFP3212.K-SET-2AKKU
~pim_attribute~Betriebsart	CS_VALUE_OperatingMode.BS / DS
~pim_attribute~EingangsspannungAC	230 V



~pim_attribute~Eingangsfrequenz	CS_VALUE_InputFrequencyHz.50 Hz
~pim_attribute~LeistungMax	7 W
~pim_attribute~LeistungDS	5,6 W
~pim_attribute~LeistungBS	0,8 W
~pim_attribute~zulaessigeUmgebungstemperaturInDS	-5 °C - 40 °C
~pim_attribute~zulaessigeUmgebungstemperaturInBS	-5 °C - 40 °C
~pim_attribute~Tiefe	73 mm
~pim_attribute~Breite	517 mm
~pim_attribute~Hoehe	296 mm
~pim_attribute~EinbaumassLaenge	176 mm
~pim_attribute~EinbaumassBreite	68 mm
~pim_attribute~EinbaumassHoehe	40 mm
~pim_attribute~Gewicht	2.67
label.zuordnungsspeicher.Gewicht inkl. Verpackung	3.32
~pim_attribute~Anschlussquerschnitt	2.5 mm <sup>2</sup>
~pim_attribute~Schalteingang	CS_VALUE_SwitchInput.Ja
~pim_attribute~Notlichtblockierung	CS_VALUE_EmergencyLightBlocking.Ja
~pim_attribute~Batterieanschluss	CS_VALUE_BatteryConnection.Stecker
~pim_attribute~Dimmfunktion	CS_VALUE_DimmingFunction.Ja
~pim_attribute~Zolltarifnummer	94056180
~pim_attribute~EAN	4260682155313



TEXT. TECHNICAL-DRAWINGS

