



## Art.-Nr: CC24-40

The state-of-the-art 24-volt low-power system is specially designed for users who want an economical solution – without compromising on safety. CoreCompact 24 impresses with its simple installation and commissioning as well as a high level of ease of operation and maintenance. A large number of intelligent functions make the system particularly operationally reliable and future-proof. Smart 24-volt emergency lighting system with automatic monitoring of the system and luminaires without a separate data line.

Easy installation and commissioning thanks to the configuration wizard with intelligent self-configuration of the luminaires. Convenient operation and monitoring via touch display and modern web interface from any end device. Luminaires can be individually programmed and dimmed for flexible adaptation to modern energy concepts. Scene control and functional tests manually or via schedules. Configurable automatic email notifications for e.g. errors, warnings and test protocols. Automatic logbook and battery discharge diagram for each test to save time in service and maintenance. High level of future-proofing thanks to the update option of all system components via the integrated USB interface. Safe emergency power supply thanks to durable and gas-free lithium iron phosphate battery. Compact, lightweight and easy to maintain.

Recommended pre-fuse 13A

Input fuse T5A

Connection cross-section 1.5 - 4mm<sup>2</sup>

2 x Lithium-iron-phosphate-battery 20Ah



Plus d'informations

[www.rp-group.com/fr/item/CC24-40](http://www.rp-group.com/fr/item/CC24-40)

## DONNÉES TECHNIQUES

Certification	CE
Nombre de circuits électriques	4
Chargeur	Oui
Nombre de modules de charge	1 pce.
Modules SAM	non
Modules IO	Oui
CCIF	Oui
Peut être mis en réseau	Oui
Sortie UPS	non



Compartiment à piles	Oui
Alimentation électrique 1 h	255 W
Alimentation électrique 3 h	190 W
Alimentation électrique 8 h	60 W
Tension d'entrée AC	230 V
Fréquence d'entrée	50 / 60 Hz
Tension de sortie AC	24 / 19,2 V
Matériau	Tôle d'acier
Couleur du boîtier	blanc
Classe de protection	IP20
Profondeur	230 mm
Largeur	250 mm
Hauteur	455 mm
Poids	9 kg
Poids avec emballage	9 kg
Numéro du tarif douanier	85371098

Au: 26.02.2025 - Sous réserve de modifications techniques et d'erreurs.