



## Art.-Nr: CC24-40

The state-of-the-art 24-volt low-power system is specially designed for users who want an economical solution – without compromising on safety. CoreCompact 24 impresses with its simple installation and commissioning as well as a high level of ease of operation and maintenance. A large number of intelligent functions make the system particularly operationally reliable and future-proof. Smart 24-volt emergency lighting system with automatic monitoring of the system and luminaires without a separate data line.

Easy installation and commissioning thanks to the configuration wizard with intelligent self-configuration of the luminaires. Convenient operation and monitoring via touch display and modern web interface from any end device. Luminaires can be individually programmed and dimmed for flexible adaptation to modern energy concepts. Scene control and functional tests manually or via schedules. Configurable automatic email notifications for e.g. errors, warnings and test protocols. Automatic logbook and battery discharge diagram for each test to save time in service and maintenance. High level of future-proofing thanks to the update option of all system components via the integrated USB interface. Safe emergency power supply thanks to durable and gas-free lithium iron phosphate battery. Compact, lightweight and easy to maintain.

Recommended pre-fuse 13A

Input fuse T5A

Connection cross-section 1.5 - 4mm<sup>2</sup>

2 x Lithium-iron-phosphate-battery 20Ah



Więcej informacji  
[www.rp-group.com/pl/item/CC24-40](http://www.rp-group.com/pl/item/CC24-40)



### DANE TECHNICZNE

Certyfikaty	CE
Liczba obwodów	4
Ładowarka	Tak
Liczba ładowarek	1 szt.
Moduł SAM	Nie
Moduł IO	Tak
CCIF	Tak
Możliwość łączenia w sieć	Tak
Wyjście do UPS	Nie



Przedział akumulatorowy	Tak
Zasilanie 1 h	255 W
Zasilanie 3h	190 W
Zasilanie 8 h	60 W
Napięcie wejściowe AC	230 V
Częstotliwość	50 / 60 Hz
Napięcie wyjściowe AC	24 / 19,2 V
Materiał	Blacha stalowa
Kolor obudowy	Biała
Klasa ochronności	IP20
Głębokość	230 mm
Szerokość	250 mm
Wysokość	455 mm
Waga	9 kg
Waga z opakowaniem	9 kg
Kod taryfy celnej	85371098

Od: 26.02.2025 - Zastrzega się prawo do zmian technicznych i błędów.