



Art.-Nr: EAQL029ML-AZ Safety luminaire Central power supply Ceiling, ML, Central power supply, , IP40, Zinc die-cast, Anthracite

LED safety light for ceiling mounting and for illuminating escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-222 and DIN EN 1838. The unobtrusive ceiling light made of zinc-aluminum adapts unobtrusively to the ceiling. Optimum light distribution and illumination of the escape and rescue routes is achieved through the use of diffuser lenses and high-performance LED ERT technology. The innovative integrated lens carrier with quick-mounting device enables the flexible use of different lens types depending on the application. Round and corridor lenses are already included in the scope of delivery for each light.





More information



TECHNICAL DATA


| Luminaire type | Safety luminaire |
|------------------------|---|
| Mounting | Ceiling |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Housing color | Anthracite |
| Protection type (IP) | IP40 |
| Impact resistance (IK) | ≥ 3 |
| Certification | Waste disposal, CE, TÜV Rheinland Type approved, ENEC |
| Insulation class | 2 |
| Supply | Central power supply |
| Monitoring | ML |
| Bridging time | Central power supply |
| Operating mode | single luminaire switching |
| Input voltageAC | 230 V |
| Input frequency | 50 / 60 Hz |
| Input voltage DC | 216 V |
| Power max. | 4,6 W |






| Power DS | 4,6 W |
|--------------------------|---------------|
| Power BS | 1,2 W |
| Depth | 104 mm |
| Width | 104 mm |
| Height | 39 mm |
| Weight | 0.31 |
| Weight incl. packaging | 0.35 |
| Connection cross-section | 2.5 mm² |
| Switching input | No |
| Emergency light blocking | No |
| Battery connection | No |
| Dimming function | Yes |
| Luminous flux mains | 360 lm |
| Luminous flux emergency | 360 lm |
| Customs tariff number | 94056180 |
| Country of origin | DEUTSCHLAND |
| EAN | 4260766552748 |

TECHNICAL DRAWING





ACCESSORY LIST

ILD-APA-02 -





RELATED PRODUCTS

| ArtNo. | lmage | Monitoring | Supply | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. Iuminaires | Single luminaire monitoring |
|------------------|-------------|----------------|-------------------------|-------|------------|------------------|----------------------|-----------------------|---------------------|--------------------------------|
| EAQL029ML | Flexi click | ML | Central power supply | | €€€ | Yes | low | Yes | 1,920 per system | central |
| EAQL529CC | Flexi click | CoreCompact 24 | Central power supply | | €€ | Yes | low | Yes | | central |
| EAQL529CC- AZ | Fleri cick | CoreCompact 24 | Central power supply | | €€ | Yes | low | Yes | | central |

As of: 27.06.2024 - Subject to technical changes and errors.