



# Art.-Nr: EERL039ML-AZ Safety luminaire Centralised power supply systems Ceiling mounting, ML, CPS, , IP20, Zinc die-cast, Anthracite

LED safety light for illuminating escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-222 and DIN EN 1838.

The recessed ceiling light made of zinc-aluminum adapts unobtrusively to the ceiling. In addition to conventional ceiling installation, it can also be installed in conventional and fire protection boxes. The status LED integrated into the lens does not interrupt the harmony of the housing. The use of diffuser lenses and powerful LED ERT technology achieves optimal light distribution and illumination of the escape and rescue routes. The innovative integrated lens carrier with quick-mounting device enables the flexible use of different lens types depending on the application. Round and corridor lenses are already included in the scope of delivery for each light.





More information



#### **TECHNICAL DATA**

Luminaire type	Safety luminaire				
Mounting	Ceiling mounting				
Pictograph	No				
Illuminant	LED				
Housing material	Zinc die-cast				
Housing color	Anthracite				
Protection type (IP)	IP20				
Impact resistance (IK)	≥ 3				
Certification	WEEE, CE, ENEC				
Insulation class	2				
Supply	Centralised power supply systems				
Monitoring	ML				
Bridging time	CPS				
Operating mode	single luminaire switching				
Input voltageAC	230 V				
Input frequency	50 / 60 Hz				
Input voltage DC	216 V				
Power max.	4,8 W				






Power DS	4,8 W
Power BS	0,7 W
Height	4 mm
Diameter	88 mm
Installation dimensions Diameter	68 mm
Weight	0.25
Weight incl. packaging	0.38
Connection cross-section	2.5 mm²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	470 lm
Luminous flux emergency	470 lm
Customs tariff number	94056180
Country of origin	DEUTSCHLAND
EAN	4260682150882





### **TECHNICAL DRAWING**



#### **ACCESSORY LIST**

LSYS-B4 -

LSYS-F4 -

LSYS-R4 -

LSYS-S4 -





## RELATED PRODUCTS

ArtNo.	lmage	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. Iuminaires	Single luminaire monitoring
EERL039ML	Flexi clicke	ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
EERL039ML-E	Flexi click	ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
EERL539CC	Flexi clicke	CoreCompact 24	Central power supply		€€	Yes	low	Yes		central
EERL539CC- AZ	Flexi clicke	CoreCompact 24	Central power supply		€€	Yes	low	Yes		central

As of: 09.07.2024 - Subject to technical changes and errors.