



Emergency luminaire Art.-No.: FMDS423SC

Robust ceiling-mounted Zinc die-cast luminaire for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 605982-22 and EN 1838. Appealing design with concealed screws.
Available for central power systems or as self-contained LED emergency luminaire. HACCP certified.




TECHNICAL DATA

Luminaire type	Emergency luminaire
Mounting	Ceiling mounted
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Colour	RAL 9003
Mechanical rating IP	65
Impact resistance IK	8
Protection class	1
Supply	Single battery
Monitoring	Self-Control
Operation time	3 h
Battery	6.4V/3.3Ah LiFeP04
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 Hz
Power consumption max.	6,7 W
Power consumption maintained	5,4 W
Power consumption non-maintained	0,9 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	58 mm
Width	262 mm
Height	188 mm
Weight	2.15 kg



Weight incl. Packaging	2.25 kg
Connection cross-section	1.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	Plug
Dimming function	No
Luminous flux mains mode	500 lm
Luminous flux emergency mode	500 lm
Customs tariff number	94056180
Country of origin	Germany
EAN	4260766556074

TECHNICAL DRAWING





ACCESSORIES

- FMDA001 - ceiling bracket, single sided white
- FMDA002 - ceiling bracket, double sided white
- FMDA001-AZ - ceiling bracket, single sided black
- FMDA002-AZ - ceiling bracket, double sided white
- FMWA001 - Surface mounting adapter for lateral cable feed
- FMFH - flexible wall mounting for FM