



Art.-Nr: KCW029-IP65
Safety luminaire Centralised power supply systems
Universal, Without monitoring, CPS, 30 m, IP65, Plastic, white

Slim convex plastic safety luminaire for wall mounting. Emergency exit sign luminaire with plug-in set of pictograms fitted on the inside without the use of solvents. Without the use of pictograms, use at the same time as a safety luminaire with the crystal-clear cover included.

The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

www.rp-group.com/en/item/KCW029-IP65



TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Universal
Recognition distance	30 m
Pictograph	No
Housing material	Plastic
Housing color	white
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Permanent circuit
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	100-254 V
Power max.	4,6 W
Power DS	4,6 W



Power BS	0 W
Ambient temperature DS	-20 °C - 40 °C
Ambient temperature BS	-20 °C - 40 °C
Depth	60 mm
Width	340 mm
Height	170 mm
Weight	0.66
Weight incl. packaging	0.75
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
EAN	4260349829281

TECHNICAL DRAWING





ACCESSORY LIST

BALL2 - Wire mesh guard

DWKCW -

KC-IP65 -

KCER - Mounting frame

KCWFH - Wall holder

As of: 04.09.2024 - Subject to technical changes and errors.