



Art.-Nr: KCW029ML-P-IP64 **Safety luminaire Centralised power supply systems** Universal, Central power supply (ML), CPS, , IP64, Plastic, white

Slim convex plastic safety luminaire for wall mounting. Emergency exit sign luminaire with plug-in set of pictograms fitted on the inside without the use of solvents. Without the use of pictograms, use at the same time as a safety luminaire with the crystal-clear cover included.

Control and monitoring via central power supply system. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.









More information www.rp-group.com/en/item/KCW029ML-P-



TECHNICAL DATA


Luminaire type	Safety luminaire			
Mounting	Universal			
Pictograph	No			
Housing material	Plastic			
Housing color	white			
Protection type (IP)	IP64			
Impact resistance (IK)	6			
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC			
Insulation class	2			
Supply	Centralised power supply systems			
Monitoring	Central power supply (ML)			
Bridging time	CPS			
Battery	/			
Operating mode	single luminaire switching			
Input voltageAC	230 V			
Input frequency	50 / 60 Hz			
Input voltage DC	216 V			
Power max.	5,2 W			






Power DS	5,2 W
Power BS	1,1 W
Ambient temperature DS	-20 °C - 40 °C
Ambient temperature BS	-20 °C - 40 °C
Depth	60 mm
Width	340 mm
Height	170 mm
Weight	0.69
Weight incl. packaging	0.78
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
EAN	4260581712631

TECHNICAL DRAWING









ACCESSORY LIST

BALL2 - Wire mesh guard

DWKCW -

KC-IP65 -

KCER - Mounting frame

KCWFH - Wall holder

RELATED PRODUCTS

ArtNo.	lmage	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
KCW029ML- IP64	₹	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central
KCW529CC- IP64	₹	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central
KCW529CC- IP65	₹	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central
KCW529CC-P- IP64	₹	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central

As of: 23.08.2024 - Subject to technical changes and errors.