



**Art.-Nr: KCW519CC-P-IP64**  
**Safety luminaire Centralised power supply systems**  
**Wall, CoreCompact 24, CPS, 30 m, IP54, Plastic, white**

Slightly curved high-grade emergency luminaire in polycarbonate for wall or ceiling mounting.

Emergency luminaire according to EN 60598-1, EN 60598-2-22 and EN 1838 norms.



More information



## TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Wall
Recognition distance	30 m
Pictograph	No
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP54
Impact resistance (IK)	6
Certification	WEEE, CE, ENEC, TÜV Rheinland Type approved
Insulation class	3
Supply	Centralised power supply systems
Monitoring	CoreCompact 24
Bridging time	CPS
Operating mode	Standby circuit / permanent circuit
Input voltageAC	24 V
Power max.	4,2 W
Power DS	4,2 W
Power BS	0,4 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C
Depth	60 mm



Width	340 mm
Height	170 mm
Weight	0.62
Weight incl. packaging	0.71
Connection cross-section	2.5 mm <sup>2</sup>
Switching input	No
Emergency light blocking	No
Battery connection	No
Luminous flux mains	335 lm
Luminous flux emergency	335 lm
Customs tariff number	94056120
EAN	4260682157300



## TECHNICAL DRAWING



## ACCESSORY LIST

- BALL2 -
- DWKCW -
- KC-IP65 -
- KCER -
- KCWFH -

As of: 22.07.2024 - Subject to technical changes and errors.