



**Art.-Nr: KCW529CC-IP65**  
**Safety luminaire Centralised power supply systems**  
**Universal, CoreCompact 24, CPS, , IP65, Plastic, white**

Slightly curved high-grade emergency luminaire in polycarbonate for wall or ceiling mounting.

Emergency luminaire according to EN 60598-1, EN 60598-2-22 and EN 1838 norms.



More information



## TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC
Insulation class	3
Supply	Centralised power supply systems
Monitoring	CoreCompact 24
Bridging time	CPS
Operating mode	Standby circuit / permanent circuit
Input voltage AC	24 V
Power max.	5,1 W
Power DS	5,1 W
Power BS	0,4 W
Ambient temperature DS	-20 °C - 40 °C
Ambient temperature BS	-20 °C - 40 °C
Depth	60 mm
Width	340 mm



Height	170 mm
Weight	0.65
Weight incl. packaging	0.74
Connection cross-section	2.5 mm <sup>2</sup>
Switching input	No
Emergency light blocking	No
Battery connection	No
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
EAN	4260682157348

## TECHNICAL DRAWING



## ACCESSORY LIST

- BALL2 -
- DWKCW -
- KC-IP65 -
- KCER -
- KCWFH -



## RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
KCW029ML-IP64		ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KCW029ML-P-IP64		ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KCW529CC-IP64		CoreCompact 24	Central power supply		€€	Yes	low	Yes		central
KCW529CC-P-IP64		CoreCompact 24	Central power supply		€€	Yes	low	Yes		central

As of: 22.07.2024 - Subject to technical changes and errors.