



Art.-Nr: KCW529CC-P-IP64
Safety luminaire Centralised power supply systems
Universal, CoreCompact 24, CPS, , IP64, Plastic, white

Slightly curved high-grade emergency luminaire in polycarbonate for wall or ceiling mounting.

Emergency luminaire according to EN 60598-1, EN 60598-2-22 and EN 1838 norms.



More information



TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP64
Impact resistance (IK)	6
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC
Insulation class	3
Supply	Centralised power supply systems
Monitoring	CoreCompact 24
Bridging time	CPS
Operating mode	Standby circuit / permanent circuit
Input voltageAC	24 V
Power max.	5,1 W
Power DS	5,1 W
Power BS	0,4 W
Ambient temperature DS	-20 °C - 40 °C
Ambient temperature BS	-20 °C - 40 °C
Depth	60 mm
Width	340 mm



Height	170 mm
Weight	0.65
Weight incl. packaging	0.74
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
EAN	4260682157362

TECHNICAL DRAWING



ACCESSORY LIST

- BALL2 -
- DWKCW -
- KC-IP65 -
- KCER -
- KCWFH -



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
KCW029ML-IP64		ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KCW029ML-P-IP64		ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KCW529CC-IP64		CoreCompact 24	Central power supply		€€	Yes	low	Yes		central
KCW529CC-IP65		CoreCompact 24	Central power supply		€€	Yes	low	Yes		central

As of: 22.07.2024 - Subject to technical changes and errors.