



### Art.-Nr: KMB413WL-TT-SW Safety luminaire Single Battery Universal, Wireless Professional (WL), 3 h, , IP54, Plastic, Black

Compact safety luminaire to illuminate escape and emergency routes with prismatic cover for optimum light distribution. This is possible thanks to the white high-power SMD LEDs, which also have a long life of around 50,000 hours. Available to connect to central battery systems and as a single-battery luminaire. When fitted with the optional installation frame, the luminaire can be elegantly countersunk into the ceiling.

Housing colour: RAL 9005 black

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.





#### More information

www.rp-group.com/en/item/KMB413WL-TT-SW



#### **TECHNICAL DATA**


| Luminaire type         | Safety luminaire                    |
|------------------------|-------------------------------------|
| Mounting               | Universal                           |
| Pictograph             | No                                  |
| Illuminant             | LED                                 |
| Housing material       | Plastic                             |
| Housing color          | Black                               |
| Protection type (IP)   | IP54                                |
| Impact resistance (IK) | ≥ 3                                 |
| Certification          | WEEE, CE                            |
| Insulation class       | 2                                   |
| Supply                 | Single Battery                      |
| Monitoring             | Wireless Professional (WL)          |
| Bridging time          | 3 h                                 |
| Battery                | LiFePO4 3,2 V/3,3 Ah                |
| Operating mode         | Standby circuit / permanent circuit |
| Input voltageAC        | 230 V                               |






| Input frequency          | 50 / 60 Hz          |
|--------------------------|---------------------|
| Input voltage DC         | - V                 |
| Power max.               | 5,3 W               |
| Power DS                 | 3,9 W               |
| Power BS                 | 1,5 W               |
| Ambient temperature DS   | -15 °C - 40 °C      |
| Ambient temperature BS   | -15 °C - 40 °C      |
| Depth                    | 250 mm              |
| Width                    | 34 mm               |
| Height                   | 50 mm               |
| Weight                   | 0.58                |
| Weight incl. packaging   | 0.65                |
| Connection cross-section | 2.5 mm <sup>2</sup> |
| Switching input          | Yes                 |
| Emergency light blocking | No                  |
| Battery connection       | Connector           |
| Dimming function         | No                  |
| Luminous flux mains      | 190 lm              |
| Luminous flux emergency  | 190 lm              |
| Customs tariff number    | 94056180            |
| EAN                      | 4262483024003       |

# TECHNICAL DRAWING











## ACCESSORY LIST

KME-EB - Mounting frame

BALL1 - Wire mesh guard

KMBE - Concrete-mounted box

BALLPLX-KMB - Wire mesh surround

KMBFH -

As of: 01.11.2024 - Subject to technical changes and errors.