



Art.-Nr: KMU411WB-3P
Exit sign Single Battery
3-phase conductor rail, Wireless Basic (WB), 1 h, 24 m, IP43,
Plastic, white

Slim convex emergency exit sign luminaire with 3-phase adapter. Planning certainty for identifying escape and emergency routes for inscription on one or two sides is provided by tool-free variable use of the pictograms on site. The pictograms are inserted without the use of solvents. The set of pictograms (arrow to the right, left, up or down) is supplied as standard.

The pre-mounted 3-phase adapter allows for tool-free installation in popular 3-phase tracks, such as Nordic Aluminium GLOBAL pro (previously NOKIA) XTS, XTTS and XTSC.

Emergency exit sign luminaire in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information
[www.rp-group.com/en/item/
KMU411WB-3P](http://www.rp-group.com/en/item/KMU411WB-3P)



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	3-phase conductor rail
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP43
Impact resistance (IK)	3



Certification	WEEE, CE
Insulation class	2
Supply	Single Battery
Monitoring	Wireless Basic (WB)
Bridging time	1 h
Battery	/
Operating mode	Standby circuit / permanent circuit
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	5,3 W
Power DS	3,9 W
Power BS	1,5 W
Ambient temperature DS	-5 °C - 35 °C
Ambient temperature BS	-5 °C - 35 °C
Depth	34 mm
Width	250 mm
Height	174 mm
Weight	0.37
Weight incl. packaging	0.54
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	190 lm
Luminous flux emergency	190 lm
Customs tariff number	94056120
EAN	4262483020241



TECHNICAL DRAWING



ACCESSORY LIST

LFP3233.01 - CS_VALUE_BatteryTechnology. Battery

As of: 23.08.2024 - Subject to technical changes and errors.