



Combined emergency luminaire Art.-No.: LFD12009-NW



The robust LED wall and ceiling luminaire made of glass fibre-reinforced polyester for damp locations is suitable for illuminating storage areas, car parks, etc. In mains operation, the luminaire has an output of up to 4,500 lm. External mounting brackets facilitate installation.

TECHNICAL DATA

| | |
|---|--------------------------------|
| Luminaire type | Combined emergency luminaire |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Polycarbonate |
| Colour | Opal |
| Mechanical rating IP | 65 |
| Impact resistance IK | 8 |
| Protection class | 1 |
| Supply | Central power supply system |
| Monitoring | None |
| Operation time | CPS |
| Operation mode | maintained/non-maintained mode |
| Input Voltage AC | 230 V |
| Input Frequency Hz | 50 / 60 Hz |
| Input Voltage DC | 216 V |
| Power consumption max. | 36 W |
| Power consumption maintained | 36 W |
| Ambient temperature maintained mode | -5 °C / 40 °C |
| Ambient temperature non-maintained mode | -5 °C / 40 °C |
| Length | 1,220 mm |
| Width | 82 mm |
| Height | 97 mm |
| Weight | 1.8 kg |
| Weight incl. Packaging | 2.05 kg |
| Connection cross-section | 1.5 mm |



| | |
|------------------------------|---------------|
| Switching input L' | Yes |
| Emergency light blocking | No |
| Battery connector | None |
| Dimming function | No |
| Luminous flux mains mode | 4500 lm |
| Luminous flux emergency mode | 4500 lm |
| Customs tariff number | 94056120 |
| Coutry of origin | CHINA |
| EAN | 4260682142085 |

TECHNICAL DRAWING

