



Art.-Nr: LFD15003SC-NW-BM
General light, Safety luminaire
Universal, SelfControl (SC), 8 h, , IP65, Polycarbonate, Light grey



The robust LED wall- and ceiling-mounted luminaire made from fibreglass-reinforced polyester for damp room applications. The external support brackets simplify mounting.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/LFD15003SC-NW-BM



TECHNICAL DATA


Luminaire type	General light, Safety luminaire
Mounting	Universal
Pictograph	No
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	CE, WEEE
Insulation class	1
Monitoring	SelfControl (SC)
Bridging time	8 h
Battery	LiFePO4 3,2 V/4,5 Ah
Power DS	54 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C
Depth	1560 mm
Width	82 mm
Height	97 mm
Weight	2.327
Weight incl. packaging	2.677
Luminous flux mains	6500 lm



Customs tariff number

94051140

TECHNICAL DRAWING



As of: 28.10.2024 - Subject to technical changes and errors.