



Combined emergency luminaire Art.-No.: LFD15003SC-NW



The robust LED wall and ceiling luminaire made of glass fibre-reinforced polyester for damp locations is suitable for illuminating storage areas, car parks, etc. In mains operation, the luminaire has an output of up to 7,000 lm. External mounting brackets facilitate installation.

TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Colour	Opal
Mechanical rating IP	65
Impact resistance IK	8
Protection class	1
Supply	Single battery
Monitoring	Self-Control
Operation time	3 h
Battery	3,2V/4,5Ah LiFeP04
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Power consumption max.	55 W
Power consumption maintained	54 W
Power consumption non-maintained	0,5 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	1,560 mm
Width	82 mm
Height	97 mm
Weight	2.327 kg
Weight incl. Packaging	2.677 kg



Connection cross-section	1.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	Plug
Dimming function	No
Luminous flux mains mode	7000 lm
Luminous flux emergency mode	500 lm
Customs tariff number	94051140
Coutry of origin	Germany
EAN	4260659566494

TECHNICAL DRAWING

