



Combined emergency luminaire Art.-No.: LFD15009ML-NW



The robust LED wall and ceiling luminaire made of glass fibre-reinforced polyester for damp locations is suitable for illuminating storage areas, car parks, etc. In mains operation, the luminaire has an output of up to 7,000 lm. External mounting brackets facilitate installation.

TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Colour	Opal
Mechanical rating IP	65
Impact resistance IK	8
Protection class	1
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	56 W
Power consumption maintained	56 W
Power consumption non-maintained	1,5 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	1,560 mm
Width	82 mm
Height	97 mm
Weight	2.2 kg
Weight incl. Packaging	2.55 kg



Connection cross-section	1.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	None
Dimming function	No
Luminous flux mains mode	6800 lm
Luminous flux emergency mode	6800 lm
Customs tariff number	94051140
Country of origin	Germany
EAN	4260682142092

TECHNICAL DRAWING

