



Art.-Nr: MCV24
multiControl plus CS_VALUE_SystemType2.Unterverteiler
CS_VALUE_HousingType.
CS_VALUE_SystemType2.Unterverteiler
CS_VALUE_HousingType.

Subdistributions separate the main system from the circuit modules.

Subdistributions offer single luminaire monitoring without additional wires like the main system.

Optional in E30 fireproof version.



general.qrcode-more-infos



TEXT. TECHNISCHE DATEN

~pim_attribute~Einschuebe	12 Stk.
anzahlstromkreise	24
~pim_attribute~Lader	CS_VALUE_ChargerIntegrated.Nein
~pim_attribute~SAMModule	CS_VALUE_SAMIntegrated.Optional
~pim_attribute~IOModule	CS_VALUE_IOIntegrated.Nein
~pim_attribute~CCIF	CS_VALUE_CCIFIntegrated.Optional
~pim_attribute~Vernetzbar	CS_VALUE_Networking.Nein
~pim_attribute~AbgangUsUv	CS_VALUE_PortUSUV.Nein
~pim_attribute~Batteriefach	CS_VALUE_BatteryCompartmentIncluded.Nein
versorgungleistung1h	3650 W
versorgungleistung3h	3650 W
versorgungleistung8h	3650 W
~pim_attribute~Eingangsfrequenz	CS_VALUE_InputFrequencyHz.50 / 60 Hz
~pim_attribute~AusgangsspannungAC	230 V
~pim_attribute~Material	CS_VALUE_Material.35
~pim_attribute~Farbe	CS_VALUE_Color.RAL 7035
~pim_attribute~Schutzklasse	CS_VALUE_IngressProtection.IP 20
~pim_attribute~Schutzklasse	CS_VALUE_IngressProtection.IP 20
~pim_attribute~Tiefe	450 mm
~pim_attribute~Breite	600 mm



~pim_attribute~Hoehe	550 mm
~pim_attribute~Gewicht	30 kg
~pim_attribute~Gewicht	30
~pim_attribute~Zolltarifnummer	85371098
~pim_attribute~Ursprungsland	DEUTSCHLAND