



Art.-Nr: MNXL130-ELS miniControl XL plus (MNXL) Central battery system Combination cabinet Central battery system, Combination cabinet, DCM, LDM, Leuchten

MAX. 32 MAINS CIRCUITS / 1.500 W, 1H / 640 LUMINAIRES

The Low Power System miniControl XL plus closes with a maximum output of 1.500 W the gap between the smaller powered miniControl XL plus and the big brother midiControl plus. Through the principle of decentralization per fire compartment, similar to a single battery system, there will be no costs for E30-powerlines and their installation. The miniControl XL plus is installed in an operating room in each fire compartment.

Batteries are not included and have to be ordered separately.



More information

TECHNICAL DATA

| Inserts | 16 pcs. |
|---------------------|-----------------------|
| Number of circuits | 30+1(Hilfsstromkreis) |
| Loader | Yes |
| Modules SAM | Yes |
| IO modules | Yes |
| CCIF | Yes |
| Connectable | Yes |
| Outgoing UPS | No |
| Battery compartment | Yes |
| Supply power 1 h | 2575 W |
| Supply power 3 h | 1245 W |
| Supply power 8 h | 570 W |
| Input voltageAC | 230 V |
| Input frequency | 50 / 60 Hz |
| Output voltage AC | 230 V |
| Material | Steel sheet |
| Housing color | RAL 7035 |





| Insulation class | IP20 |
|-----------------------|----------|
| Insulation class | IP20 |
| Depth | 230 mm |
| Width | 571 mm |
| Height | 1470 mm |
| Weight | 49.8 kg |
| Weight | 49.8 |
| Customs tariff number | 85371098 |

As of: 11.07.2024 - Subject to technical changes and errors.