



Art.-Nr: PFD411WL-TT
Exit sign Single Battery
Ceiling, Wireless Professional (WL), 1 h, 24 m, IP65, Plastic,
white

Trapezoid, plastic emergency exit sign luminaire for fitting on the ceiling for inscription on one or two sides with self-adhesive pictogram.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information
www.rp-group.com/en/item/PFD411WL-TT



TECHNICAL DATA




Luminaire type	Exit sign
Mounting	Ceiling
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	WEEE, CE, D-Sign
Insulation class	1
Supply	Single Battery
Monitoring	Wireless Professional (WL)
Bridging time	1 h
Battery	/
Operating mode	Standby circuit / permanent circuit
Input voltageAC	230 V



Input frequency	50 Hz
Power max.	5,5 W
Power DS	3,6 W
Power BS	0,7 W
Ambient temperature DS	-15 °C - 40 °C
Ambient temperature BS	-15 °C - 40 °C
Depth	152 mm
Width	370 mm
Height	195 mm
Weight	0.92
Weight incl. packaging	1.05
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
EAN	4260766558344



TECHNICAL DRAWING



ACCESSORY LIST

- 2PW-EB - Pendant
- 2DW-EB -
- DSA - Wire suspension
- PFER -

As of: 23.08.2024 - Subject to technical changes and errors.