



Art.-Nr: PMW428SC-TT Safety luminaire Universal, SelfControl (SC), , , IP65, Plastic, white

Plastic safety luminaire with convex shaped surround.

To help with mounting, levelling screws are integrated to compensate for uneven surfaces.

The luminaire can be mounted by fitting on the wall and ceiling as well as fitting in the ceiling in conjunction with the mounting frame available.

Automatic monitoring of safety luminaire with SelfControl. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.









TECHNICAL DATA


Luminaire type	Safety luminaire
Mounting	Universal
Pictograph	No
Housing material	Plastic
Housing color	white
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	CE, WEEE, D-Sign
Insulation class	2
Monitoring	SelfControl (SC)
Battery	/
Ambient temperature DS	-15 °C - 40 °C
Ambient temperature BS	-15 °C - 40 °C
Depth	65 mm
Width	236 mm
Height	136 mm
Weight	0.6
Weight incl. packaging	0.73







EAN 4262483023174

TECHNICAL DRAWING











ACCESSORY LIST

LSYS-B4 -

LSYS-F4 -

LSYS-H4-

LSYS-R4 -

LSYS-S4 -

LSYS-WF4 -

As of: 04.11.2024 - Subject to technical changes and errors.