



Art.-Nr: PXD019ML

Exit sign Centralised power supply systems

**Surface mounting, Central power supply (ML), CPS, 30 m,
IP65, PCABS, Polycarbonate, White**

Design and function-optimized convex exit sign with a clear, closed cover that tapers symmetrically towards the bottom. The screwed cover ensures stability and a high IP protection class, while the functional technology remains unobtrusive and no screws are visible from the outside. The pictograms are on the inside and are inserted solvent-free for one- or two-sided labeling.

Control and monitoring via central power supply system. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (2x man in the door and 2 straight arrows) are supplied as standard.



More information

www.rp-group.com/en/item/PXD019ML



TECHNICAL DATA

| | |
|------------------------|----------------------------------|
| Luminaire type | Exit sign |
| Mounting | Surface mounting |
| Recognition distance | 30 m |
| Pictograph | Set |
| Illuminant | LED |
| Housing material | PCABS, Polycarbonate |
| Housing color | White |
| Protection type (IP) | IP65 |
| Impact resistance (IK) | 6 |
| Certification | CE, WEEE, D-Sign |
| Insulation class | 2 |
| Supply | Centralised power supply systems |
| Monitoring | Central power supply (ML) |
| Bridging time | CPS |
| Battery | / |
| Operating mode | single luminaire switching |
| Input voltageAC | 230 V |



| | |
|---|---------------------|
| Input frequency | 50 / 60 Hz |
| Input voltage DC | 216 V |
| Power max. | 5,2 W |
| Power maintained | 5,2 W |
| Power non-maintained | 1,1 W |
| Ambient temperature maintained mode | -20 °C to 40 °C |
| Ambient temperature non-maintained mode | -20 °C to 40 °C |
| Depth | 73 mm |
| Width | 339 mm |
| Height | 211 mm |
| Weight | 1.37 |
| Weight incl. packaging | 1.47 |
| Connection cross-section | 2.5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | No |
| Dimming function | Yes |
| Luminous flux mains | 335 lm |
| Luminous flux emergency | 335 lm |
| Customs tariff number | 94056180 |
| EAN | 4262483025819 |

ACCESSORY LIST

PXD-AW -

As of: 21.05.2025 - Subject to technical changes and errors.