



Art.-Nr: QAW423WL-BM-SIWW

**General light, Safety luminaire Single Battery
Universal, Wireless Professional (WL), 3 h, , IP20, Aluminium,
white**

Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. The LED-luminaire is operated with 26W, 2.300lm and light colour 3000 Kelvin. The general light is switched independently of the emergency light via the motion detector, which is not visible from the outside.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional.



More information

www.rp-group.com/en/item/QAW423WL-BM-SIWW



TECHNICAL DATA

| | |
|------------------------|-------------------------------------|
| Luminaire type | General light, Safety luminaire |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Aluminium |
| Housing color | white |
| Protection type (IP) | IP20 |
| Impact resistance (IK) | ≥ 3 |
| Certification | WEEE, CE |
| Insulation class | 1 |
| Supply | Single Battery |
| Monitoring | Wireless Professional (WL) |
| Bridging time | 3 h |
| Battery | LiFePO4 3,2V V/3,3 Ah |
| Operating mode | Standby circuit / permanent circuit |
| Input voltageAC | 230 V |
| Input frequency | 50 / 60 Hz |
| Power max. | 30 W |
| Power DS | 26,4 W |



| | |
|--------------------------|---------------------|
| Power BS | 0,4 W |
| Ambient temperature DS | -5 °C - 30 °C |
| Ambient temperature BS | -5 °C - 35 °C |
| Height | 113 mm |
| Diameter | 395 mm |
| Weight | 0.78 |
| Weight incl. packaging | 1.1 |
| Connection cross-section | 2.5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Connector |
| Dimming function | Yes |
| Luminous flux mains | 2300 lm |
| Luminous flux emergency | 250 lm |
| Customs tariff number | 94056180 |
| EAN | 4260682159908 |



TECHNICAL DRAWING



As of: 01.10.2024 - Subject to technical changes and errors.