



Art.-Nr: QBW529CC
General light, Safety luminaire Centralised power supply systems
Universal, CoreCompact 24 (CC), CPS, , IP44, Plastic, white

Round plastic LED general-purpose luminaire, as combined safety luminaire in a timeless design.

Alongside the general-purpose lighting, it also includes an integrated safety light function. When mounting, the emergency light LED can be swung out without the need for tools, to perfectly illuminate the escape and emergency routes when mounted on a wall, for example.

Control and monitoring via central 24 V low-power system.



More information

www.rp-group.com/en/item/QBW529CC



TECHNICAL DATA

| | |
|------------------------|-------------------------------------|
| Luminaire type | General light, Safety luminaire |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Plastic |
| Housing color | white |
| Protection type (IP) | IP44 |
| Impact resistance (IK) | 6 |
| Certification | WEEE, CE |
| Insulation class | 2 |
| Supply | Centralised power supply systems |
| Monitoring | CoreCompact 24 (CC) |
| Bridging time | CPS |
| Battery | / |
| Operating mode | Standby circuit / permanent circuit |
| Input voltageAC | 24 V |
| Power max. | 19 W |
| Power DS | 17 W |
| Power BS | 0,4 W |



| | |
|--------------------------|---------------------|
| Ambient temperature DS | -5 °C to 40 °C |
| Ambient temperature BS | -5 °C to 40 °C |
| Height | 98 mm |
| Diameter | 339 mm |
| Weight | 1.4 |
| Weight incl. packaging | 1.62 |
| Connection cross-section | 2.5 mm ² |
| Switching input | No |
| Emergency light blocking | No |
| Battery connection | No |
| Luminous flux mains | 1800 lm |
| Luminous flux emergency | 470 lm |
| Customs tariff number | 94056180 |
| EAN | 4262483023631 |



TECHNICAL DRAWING

QBW



QBW



As of: 20.01.2025 - Subject to technical changes and errors.