



Art.-Nr: QCW423SC-BM
General light, Safety luminaire Supply
Universal, SelfControl (SC), 3 h , IP54, Zinc die-cast, white

Round zinc die-cast luminaire with integrated motion detector for general-purpose lighting and illuminating escape and emergency routes in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

A robust variant in a timeless design, suited to indoor and outdoor use. When mounting, the emergency light LED can be swung out without the need for tools, to perfectly illuminate the escape and emergency routes when mounted on a wall, for example.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/QCW423SC-BM



TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	white
Protection type (IP)	IP54
Impact resistance (IK)	10
Certification	WEEE, CE, D-Sign
Insulation class	1
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 6,4 V/3,3 Ah
Power max.	19,3 W
Power DS	17,7 W
Power BS	1,4 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C
Height	106 mm



Diameter	363 mm
Weight	2.73
Weight incl. packaging	3.06
Luminous flux mains	1600 lm
Luminous flux emergency	470 lm
Customs tariff number	94056180
EAN	4260766559419



TECHNICAL DRAWING

QCW



QCW



As of: 29.10.2024 - Subject to technical changes and errors.