



Art.-Nr: QCW428SC-BM
General light, Safety luminaire Supply
Universal, SelfControl (SC), 8 h , IP54, Zinc die-cast, white

Round zinc die-cast luminaire with integrated motion detector for general-purpose lighting and illuminating escape and emergency routes in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

A robust variant in a timeless design, suited to indoor and outdoor use. When mounting, the emergency light LED can be swung out without the need for tools, to perfectly illuminate the escape and emergency routes when mounted on a wall, for example.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/QCW428SC-BM



TECHNICAL DATA

| | |
|------------------------|---------------------------------|
| Luminaire type | General light, Safety luminaire |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Housing color | white |
| Protection type (IP) | IP54 |
| Impact resistance (IK) | 10 |
| Certification | WEEE, CE, D-Sign |
| Insulation class | 1 |
| Monitoring | SelfControl (SC) |
| Bridging time | 8 h |
| Battery | LiFePO4 6,4 V/3,3 Ah |
| Power max. | 19,3 W |
| Power DS | 17,7 W |
| Power BS | 1,4 W |
| Ambient temperature DS | -5 °C - 40 °C |
| Ambient temperature BS | -5 °C - 40 °C |
| Height | 106 mm |



| | |
|-------------------------|---------------|
| Diameter | 363 mm |
| Weight | 2.73 |
| Weight incl. packaging | 3.06 |
| Luminous flux mains | 1600 lm |
| Luminous flux emergency | 190 lm |
| Customs tariff number | 94056180 |
| EAN | 4262483023327 |



TECHNICAL DRAWING

QCW



QCW



As of: 11.11.2024 - Subject to technical changes and errors.