



Art.-Nr: ROPA4201SC-WW
General light, Safety luminaire Single Battery
Ceiling mounting, SelfControl (SC), 3 h, , IP20,

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/ROPA4201SC-WW



TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Single Battery
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	/
Operating mode	Standby circuit / permanent circuit
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	33 W
Power DS	33 W
Power BS	2 W
Ambient temperature DS	0 °C - 40 °C
Ambient temperature BS	0 °C - 40 °C
Weight	0.1



Weight incl. packaging	0.18
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	4000 lm
Luminous flux emergency	600 lm
Customs tariff number	94056120
EAN	4260682142412

As of: 23.08.2024 - Subject to technical changes and errors.