



## Art.-Nr: WQX411WL

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional.

More information

[www.rp-group.com/en/item/WQX411WL](http://www.rp-group.com/en/item/WQX411WL)



### TECHNICAL DATA

|                          |                                     |
|--------------------------|-------------------------------------|
| Luminaire type           | Exit sign                           |
| Mounting                 | Recessed mounting                   |
| Pictograph               | Set                                 |
| Illuminant               | LED                                 |
| Insulation class         | 2                                   |
| Supply                   | Single Battery                      |
| Monitoring               | Wireless Professional (WL)          |
| Bridging time            | 1 h                                 |
| Battery                  | LiFePO4 6,4 V/1,6 Ah                |
| Operating mode           | Standby circuit / permanent circuit |
| Input voltageAC          | 230 V                               |
| Input frequency          | 50 Hz                               |
| Power max.               | 7,5 W                               |
| Power DS                 | 5,7 W                               |
| Power BS                 | 0,8 W                               |
| Ambient temperature DS   | -5 °C - 40 °C                       |
| Ambient temperature BS   | -5 °C - 40 °C                       |
| Weight                   | 0.17                                |
| Weight incl. packaging   | 0.17                                |
| Connection cross-section | 2.5 mm <sup>2</sup>                 |
| Switching input          | Yes                                 |
| Emergency light blocking | Yes                                 |
| Battery connection       | Connector                           |
| Dimming function         | Yes                                 |
| Luminous flux mains      | 250 lm                              |



|                         |               |
|-------------------------|---------------|
| Luminous flux emergency | 520 lm        |
| Customs tariff number   | 94056180      |
| EAN                     | 4260682148100 |

As of: 28.10.2024 - Subject to technical changes and errors.