



**Art.-Nr: XPIU411SC**  
**Emergency light Self-contained**  
**Universal, 1 h, , IP66, Aluminum die-cast, Polycarbonate,**  
**Yellow (RAL 1003)**

Polycarbonate cylinder safety luminaire with explosion protection for gas and dust Ex zones.

Prepared for two cable entries for feed-through wiring. By attaching a pictogram, can also be used as an emergency exit sign luminaire.

By means of mounting adapter for wall/ceiling mounting or suspension by means of eye bolt.

Labelling according to 2014/34/EC (ATEX)

Zone 1 / zone 21 gas and dust

- Ex d IIB T6 Gb / Ex d IIB T6 Gb
- Ex t IIIC T85°C Db

Manufactured in accordance with

-EN 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

-Certified by INERIS 20ATEX0005X



More information

[www.rp-group.com/en/item/XPIU411SC](http://www.rp-group.com/en/item/XPIU411SC)



## TECHNICAL DATA


Luminaire type	Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum die-cast, Polycarbonate
Housing color	Yellow (RAL 1003)
Protection type (IP)	IP66
Impact resistance (IK)	10
Certification	WEEE, CE, Explosion-protected
Insulation class	1
Supply	Self-contained
Bridging time	1 h
Battery	LiFePO4 3,2 V/



Operating mode	Non-maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Power max.	24 W
Power maintained	24 W
Ambient temperature maintained mode	0 °C to 50 °C
Ambient temperature non-maintained mode	0 °C to 50 °C
Depth	485 mm
Width	157 mm
Height	197 mm
Weight	4.28
Weight incl. packaging	4.78
Connection cross-section	2.5 mm <sup>2</sup>
Switching input	No
Emergency light blocking	Yes
Battery connection	Clip
Dimming function	No
Luminous flux mains	2400 lm
Luminous flux emergency	840 lm
Customs tariff number	94051190
EAN	4262483026878



## TECHNICAL DRAWING



## ACCESSORY LIST

X-KE001 -  
X-MB001 -  
X-KO001 -  
X4N -

As of: 23.05.2025 - Subject to technical changes and errors.