



Art.-No.: YMOCA-DIMM-MINI CASA Dimm Mini Phasenabschnitt-

NEW! Expected to be available from 01.10.2024

The CASA DIMM Mini is specially designed for flush mounting and controls phase-cut dimmable luminaires/drivers. Output power: 200W LED. It is wirelessly controlled using the CASAMBI® app.



DANE TECHNICZNE

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Consumption standby	0,5 W
Output max.	200 W
Connection cross section	1,5 mm ²
Load types	Capacitive load
Communication type	Wireless, Casambi
Dimming	TRIAC
Frequency band	2,403 - 2,479 GHz
max. transmission power	+4 dBm
CASAMBI Ready	Yes
CASAMBI Inside	Yes
Acceptance tests	
Certifications	CE, ROHS
Ingress protection (IP) rating	IP 20
Ambient temperature	-20 to +50 C°
Storage temperature	-25 to +75 C°
Housing temperatur max., tc	70 C°



Physical data	
Housing material	Tworzywo sztuczne
Housing colour	white
Length (L)	50 mm
Width (B)	48 mm
Height (H)	21,6 mm
Weight incl. Packaging	0,05 kg
Packaging Length (L)	60 mm
Packaging Width (B)	60 mm
Packaging Height (H)	34 mm