



Art.-No.: YMOCA-ROLLO-MINI-LR CASA Rollo Mini

NEW! Expected to be available from 01.10.2024

The CASA ROLLO Mini Module is specially designed for flush mounting and offers convenient control of shutters, blinds, or awnings via the configurable button or the practical app. With the additional "Long Range" feature, you can now enjoy reliable control from greater distances.



DANE TECHNICZNE

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Consumption standby	0,2 W
Connection cross section	1,5 mm ²
Switch cycles	50 000
Load types	Inductive load
Communication type	Wireless, Casambi
Switching output	345 VA
Frequency band	2,403 - 2,479 GHz
max. transmission power	+4 dBm
CASAMBI Ready	Yes
CASAMBI Inside	Yes
Acceptance tests	
Certifications	CE, ROHS
Ingress protection (IP) rating	IP 20
Ambient temperature	-20 to +50 C°
Storage temperature	-25 to +75 C°
Housing temperatur max., tc	60 C°



Physical data	
Length (L)	50 mm
Width (B)	48 mm
Height (H)	30 mm
Weight incl. Packaging	0,1 kg
Packaging Length (L)	60 mm
Packaging Width (B)	60 mm
Packaging Height (H)	34 mm