



Art.-Nr: YMOCA-T-7 Panel T 7 Casambi

Room control device with Casambi wireless interface for intuitive lighting control, equipped with sensors for temperature, humidity, and CO2, operable via a 3.5" display with a rotary-push button and configurable through the Casambi app

Room control device with Casambi wireless interface for intuitive lighting control of Casambi ecosystem participants, with up to three integrated sensors for detecting room temperature, humidity, and CO2. Scenes can be activated, or lights switched on via a 3.5" display with a rotary-push button. The simple configuration via the Casambi app allows for device-specific settings or the configuration of scenes and lighting functions with Casambi wireless.



More information www.rp-group.com/en/item/YMOCA-T-7



TECHNICAL DATA

Dimensions	
	163 mm
Product dimensions Length	103 11111
Product dimensions Width	106 mm
Product dimensions Height	28 mm
Packaging dimensions	
Packaging dimensions Length	170 mm
Packaging dimensions Width	110 mm
Packaging dimensions Height	45 mm
Color	
Color	white
Housing material	
Housing material	Plastic, Aluminium
Temperatures	
Ambient temperature (Min)	0 °C
Ambient temperature (Max)	+50 °C
CASAMBI Products	





Product.Casambi-Products.MaxPower	2 W
Input voltage DC	24 V
External power supply unit	Yes
Communication type	Bluetooth, CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
Product.Casambi-Products.BuildingAutomation	Optional Modbus, BACnet, KNX (TP)
CASAMBI Repeater	Yes
Certifications	CE
CASAMBI Connection	
Product.Casambi-Products-Connection.MountingMethod	Wall
Product.Casambi-Products- Connection.ConnectionCrossSection	1,5 mm²

As of: 26.09.2024 - Subject to technical changes and errors.