



Art.-Nr: YWDHU-RPND-3001-D
LED pendant luminaire "HUGO", ceiling surface mounting,
round, 400x87mm, 30W, 3550lm, 4000K, CRI >80, IP40,
white, Dali dimmable

LED ceiling- and wall-mounted luminaire, HUGO series, as the basic lighting for rooms in a commercial environment and at home. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI Bluetooth control available. DC compatible.



Mer informasjon



TEKNISKE DATA


Dimensjoner	
diameter	400 mm
Produktmål høyde	87 mm
Produktvekt	4 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	505 mm
Emballasjemål bredde	405 mm
Emballasjemål høyde	100 mm
Vekt inkludert emballasje	4.2 kg
Farge	
Farge	Hvit
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	CE, ENEC
beskyttelses klasse	1
IP-beskyttelse)	IP40
Glødetrådtest	650°C
Elektrisk forbindelse	
Tilkoblingstverrsnitt	1.5 mm ²
Dimming type	DALI



Systemytelse	30 W
Inngangsspenning AC	220-240V / 50-60Hz V
Startstrøm	35 A
Maktfaktor	0.98 PF
Innkoblingstid	170 µs
Strømforsyning	
Antall strømforsyninger på LS B10A	13 Stk.
Antall strømforsyninger på LS B16A	22 Stk.
Antall strømforsyninger på LS C10A	21 Stk.
Antall strømforsyninger på LS C16A	36 Stk.
DC-egnethet	Ja
Elektrisk versjon	Dimbar, med intern driftsenhet
Lystekniske data	
lyskilde	LED
Nominell lysstrøm	3550 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	3
Strålevinkel	105,6/106 °
fargetemperatur	4000 K
lys farge	840
UGR	24.1
levetid	50000 h, L80
lyseffekt	118 lm/w
temperaturer	
Omgivelsestemperatur (min)	0 °C
Omgivelsestemperatur (maks.)	+25 °C
Monteringstype	
Monteringstype	Pendel




TEXT.LICHTVERTEILUNG



cd/klm

$\eta = 100\%$

— C0 - C180 — C90 - C270



stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.