



**Art.-Nr: YWDHU-RPWD-4301-D**  
**LED pendant luminaire "HUGO", ceiling surface mounting,**  
**round, 600x87mm, 43W, 5600lm, 3000K, CRI >80, IP40,**  
**white, Dali dimmable**

LED ceiling- and wall-mounted luminaire, HUGO series, as the basic lighting for rooms in a commercial environment and at home. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI Bluetooth control available. DC compatible.



Mer informasjon



## TEKNISKE DATA


Dimensjoner	
diameter	600 mm
Produktmål høyde	87 mm
Produktvekt	7.5 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	610 mm
Emballasjemål bredde	610 mm
Emballasjemål høyde	100 mm
Vekt inkludert emballasje	7.8 kg
Farge	
Farge	Hvit
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	ENEC, CE
beskyttelses klasse	1
IP-beskyttelse)	IP40
Glødetrådtest	650°C
Elektrisk forbindelse	
Tilkoblingstverrsnitt	1.5 mm <sup>2</sup>
Dimming type	DALI



Systemytelse	43 W
Inngangsspenning AC	220-240V / 50-60Hz V
Startstrøm	20 A
Maktfaktor	0.95 PF
<b>Strømforsyning</b>	
Antall strømforsyninger på LS B10A	15 Stk.
Antall strømforsyninger på LS B16A	24 Stk.
Antall strømforsyninger på LS C10A	24 Stk.
Antall strømforsyninger på LS C16A	40 Stk.
DC-egnethet	Ja
Elektrisk versjon	med intern driftsenhet, Dimbar
<b>Lystekniske data</b>	
lyskilde	LED
Nominell lysstrøm	5600 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	3
Strålevinkel	105,6/106 °
fargetemperatur	3000 K
lys farge	830
UGR	22.8
levetid	50000 h, L80
lyseffekt	130 lm/w
<b>temperaturer</b>	
Omgivelsestemperatur (min)	0 °C
Omgivelsestemperatur (maks.)	+25 °C
<b>Monteringstype</b>	
Monteringstype	Pendel




TEXT.LICHTVERTEILUNG



cd/klm

$\eta = 100\%$

— C0 - C180    — C90 - C270



stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.