




Art.-Nr: YWDMA-LEWS-2601-D
LED luminaire "MAVS", ceiling recessed mounting,
rectangular, 865x79x79mm, 26W, 2600lm, 3000K, CRI >80,
IP40, white, switchable

LED ceiling- and wall-mounted luminaire, MAVS. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI® Bluetooth control available. DC compatible.



Mer informasjon



TEKNISKE DATA



Dimensjoner	
Produktdimensjoner lengde	865 mm
Produktdimensjoner bredde	79 mm
Produktmål høyde	79 mm
Produktvekt	2.3 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	1300 mm
Emballasjemål bredde	118 mm
Emballasjemål høyde	75 mm
Vekt inkludert emballasje	2.6 kg
CS_GROUP.CutoutDimensions	
Installasjonsdybde	150 mm
Farge	
Farge	Sølv
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	CE
beskyttelses klasse	1
IP-beskyttelse)	IP40



Elektrisk forbindelse	
Tilkoblingstverrsnitt	2.5 mm ²
Systemytelse	26 W
Inngangsspenning AC	220-240V / 50-60Hz V
Startstrøm	29 A
Maktfaktor	0.9 PF
Innkoblingstid	143 µs
Strømforsyning	
Antall strømforsyninger på LS C16A	42 Stk.
DC-egnethet	Ja
Elektrisk versjon	med intern driftsenhet, Byttbar
Lystekniske data	
lyskilde	LED
Nominell lysstrøm	2600 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	3
Strålevinkel	60 °
fargetemperatur	3000 K
lys farge	830
UGR	26.2
levetid	75000 h, L80
lyseffekt	100 lm/w
temperaturer	
Omgivelsestemperatur (min)	-20 °C
Omgivelsestemperatur (maks.)	+30 °C
Monteringstype	
Monteringstype	Takmontering



TEXT.LICHTVERTEILUNG





TILBEHØRSLISTE

YWDMA-MONKL-E - Mounting clamp for MAVS, recessed mounting / 1 pc.

stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.