



Art.-Nr: YWDPO-RENS-7201-D
LED luminaire "PORIO", wall / ceiling recessed mounting,
round, 664x125mm, 72W, 7100lm, 4000K, CRI >80, IP20,
white, switchable

LED ceiling- and wall-mounted luminaire, PORIO series, recessed design, as the basic lighting for commercial and residential rooms. Housing made from steel plate, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI Bluetooth control available. DC compatible.



Mer informasjon



TEKNISKE DATA


Dimensjoner	
diameter	664 mm
Produktmål høyde	90 mm
Produktvekt	9.4 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	680 mm
Emballasjemål bredde	680 mm
Emballasjemål høyde	140 mm
Vekt inkludert emballasje	9.6 kg
Farge	
Farge	Hvit
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	CE
beskyttelses klasse	1
IP-beskyttelse)	IP20
Glødetrådtest	650°C
Elektrisk forbindelse	
Tilkoblingstverrsnitt	1.5 mm ²



Systemytelse	72 W
Inngangsspenning AC	220-240V / 50-60Hz V
Maktfaktor	0.95 PF
Strømforsyning	
Antall strømforsyninger på LS B10A	6 Stk.
Antall strømforsyninger på LS B16A	11 Stk.
Antall strømforsyninger på LS C10A	10 Stk.
Antall strømforsyninger på LS C16A	18 Stk.
DC-egnethet	Ja
Elektrisk versjon	med intern driftsenhet, Byttbar
Lystekniske data	
lyskilde	LED
Nominell lysstrøm	7100 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	3
Strålevinkel	87,6 °
fargetemperatur	4000 K
lys farge	840
UGR	20.9
levetid	50000 h, L80
lyseffekt	99 lm/w
temperaturer	
Omgivelsestemperatur (min)	0 °C
Omgivelsestemperatur (maks.)	+25 °C
Monteringstype	
Monteringstype	Takmontering





TEXT.LICHTVERTEILUNG



cd/klm

$\eta = 100\%$

— C0 - C180 — C90 - C270



stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.