



Art.-Nr: YWDRO-RPWS-2801-D
LED pendant luminaire "RONDO", c-surface mounting, direct/indirect distribution, round, 400x62mm, 28W, 3350lm, 3000K, CRI >80, IP40, white, switchable

LED ceiling- and wall-mounted luminaire, RONDO series, with direct/indirect beam, as the basic lighting for rooms in a commercial environment and at home. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI Bluetooth control available. DC compatible.



[Mer informasjon](#)

TEKNISKE DATA


Dimensjoner	
diameter	400 mm
Produktmål høyde	62 mm
Produktvekt	3.8 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	505 mm
Emballasjemål bredde	405 mm
Emballasjemål høyde	100 mm
Vekt inkludert emballasje	4 kg
Farge	
Farge	Hvit
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	CE, ENEC
beskyttelses klasse	1
IP-beskyttelse)	IP40
Glødetrådtest	650°C
Elektrisk forbindelse	



Tilkoblingstverrsnitt	1.5 mm ²
Systemytelse	28 W
Startstrøm	23 A
Maktfaktor	0.97 PF
Innkoblingstid	140 µs
Strømforsyning	
Antall strømforsyninger på LS B10A	23 Stk.
Antall strømforsyninger på LS B16A	38 Stk.
Antall strømforsyninger på LS C10A	39 Stk.
Antall strømforsyninger på LS C16A	64 Stk.
DC-egnethet	Ja
Elektrisk versjon	med intern driftsenhet, Byttbar
Lystekniske data	
lyskilde	LED
Nominell lysstrøm	3350 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	3
Strålevinkel	105,6/106 °
fargetemperatur	3000 K
lys farge	830
UGR	23.9
levetid	50000 h, L80
lyseffekt	120 lm/w
temperaturer	
Omgivelsestemperatur (min)	0 °C
Omgivelsestemperatur (maks.)	+25 °C
Monteringstype	
Monteringstype	Pendel




TEXT.LICHTVERTEILUNG



cd/klm

$\eta = 100\%$

— C0 - C180 — C90 - C270



stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.