




Art.-Nr: YWDZO-PANS-2201-DU
LED pendant luminaire "ZOLA", ceiling surface mounting,
direct distribution, 1135x50x125mm, 22W, 2750lm, 4000K,
CRI >80, IP20, UGR <19, switchable

LED ceiling luminaire, ZOLA series, with direct and direct/indirect beam. Housing made from aluminium, white, powder-coated. Parabolic louvre diffuser, matt. Operating unit can be switched or dimmed (DALI dimmer), integrated. UGR < 16 and screen-compliant in accordance with EN 12464-1. Version with CASAMBI Bluetooth control available. DC compatible.



Mer informasjon



TEKNISKE DATA


Dimensjoner	
Produktdimensjoner lengde	1135 mm
Produktdimensjoner bredde	50 mm
Produktmål høyde	125 mm
Produktvekt	3.1 kg
Emballasjedimensjoner	
Emballasjedimensjoner lengde	1270 mm
Emballasjemål bredde	130 mm
Emballasjemål høyde	60 mm
Vekt inkludert emballasje	3.3 kg
Farge	
Farge	Hvit
Koffertmateriale	
Koffertmateriale	aluminium
Sertifisering	
Sertifisering	CE
beskyttelses klasse	1
IP-beskyttelse)	IP20
Glødetrådtest	650°C
Elektrisk forbindelse	



Tilkoblingstverrsnitt	1.5 mm ²
Systemytelse	22 W
Inngangsspenning AC	220-240V / 50-60Hz V
Startstrøm	41 A
Maktfaktor	0.95 PF
Strømforsyning	
Antall strømforsyninger på LS B10A	16 Stk.
Antall strømforsyninger på LS B16A	26 Stk.
Antall strømforsyninger på LS C10A	26 Stk.
Antall strømforsyninger på LS C16A	43 Stk.
DC-egnethet	Ja
Elektrisk versjon	med intern driftsenhet, Byttbar
Lystekniske data	
lyskilde	LED
Nominell lysstrøm	2750 lm
Fargegjengivelsesindeks	> 80 Ra
Fargetoleranse	2
Strålevinkel	72,8/64,8 °
fargetemperatur	4000 K
lys farge	840
UGR	14.4
levetid	50000 h, L80
lyseffekt	125 lm/w
temperaturer	
Omgivelsestemperatur (min)	0 °C
Omgivelsestemperatur (maks.)	+25 °C
Monteringstype	
Monteringstype	Pendel



TEXT.LICHTVERTEILUNG





stand: 21.06.2024 - Det tas forbehold om tekniske endringer og feil.